

Product information

Power Steering Oil Leak Stop

PI 18/11/02/2020



Description

Due to the additives contained, rubber and plastic seals in steering gears receive optimal care. Leaks in gears caused by hardened or brittle seals are prevented or remedied. In addition, holes and ducts in the gears are cleaned and the performance of the oil is revitalized. The noise levels of power steering systems are reduced. Using Power Steering Oil Leak Stop, the service life of steering gears can be lengthened and repair costs reduced.

Properties

- minimizes unwanted noise
- cleans and maintains
- regenerates seals
- prevents rapid aging of oil
- prevents oil loss
- good corrosion protection
- increases service life

Technical data

Color / appearance	braun / brown
Viscosity at 104 °F	~ 166 mm ² /s DIN 51562
Viscosity at 212°F	~ 26 mm ² /s DIN 51562
Density	0,888 g/ml
Refractive index at 68 °F	~ 1,478
Form	flüssig / liquid
Odor	charakteristisch / characteristic

Areas of application

Suitable for steering gears that are filled with ATF II, ATF III, ATF VI or central hydraulic system oils.

Application

Add to the compensating reservoir of the steering system. 35 ml is sufficient for 1 liter (0.3 gal.) of oil.



Available pack sizes

35 ml Tube plastic

20284

USA AND CANADA (-EN-
F-)

Our information is based on thorough research and may be considered reliable, although not legally binding.