

Speed Tec Diesel

Description

Speed Tec Diesel is a new diesel fuel additive for combustion improvement and the faster acceleration associated with it, above all in partial load range. Fully compatible with all conventional diesel and biodiesel fuels. Speed Tec Diesel considerably improves vehicle acceleration.

Properties

- improves the acceleration
- contains no organometallic compounds
- reduces frictional losses
- cleans the injection system
- better drivability
- suitable for diesel particulate filters
- tested for catalytic converters
- higher performance gain
- does not influence the cetane number

Technical data

| | |
|--------------------|---|
| Base | Additiv-Kombination / Additive combination |
| Color / appearance | klar, rötlich / clear, redish |
| Flash point | 63 °C |
| Form | flüssig / liquid |
| Viscosity at 40 °C | <7 mm ² /s |
| Odor | charkteristisch / characteristic |
| Density at 15 °C | 0,817 g/cm ³ |

Areas of application

Add to diesel fuel, especially for vehicle diesel engines as well as suitable for fast vans. For the improvement of vehicle acceleration and smooth operation.

Application

One 250 ml can is sufficient for max. 70 liters of diesel fuel. Mix the contents of the can with the diesel fuel. Mixing also takes place automatically.



Available pack sizes

| | |
|------------------------|-----------------------|
| 250 ml Can sheet metal | 3722 D-GB-I-E-P |
| 250 ml Can sheet metal | 2367 GB-DK-FIN-N-S |

Our information is based on thorough research and may be considered reliable, although not legally binding.