

# Product information

## Diesel Particulate Filter Protector

PI 46/14/09/2020



### Description

Reduces soot formation during combustion, which improves engine performance and reduces emissions. Reduces premature DPF soot clogging while extending regeneration intervals.

### Properties

- regeneration aid for diesel particulate filters
- promotes optimum combustion
- reduces soot emissions
- especially suitable for short trips and city vehicles
- protects the diesel particulate filter

### Technical data

Base	Additiv-Kombination in Trägerflüssigkeit / additive combination in carrier liquid
Color / appearance	schwarz, braun, rot / black, brown, red
Density at 59 °F	0,7989 g/cm <sup>3</sup>
Flash point	>145 °F
Viscosity at 104 °F	<7 mm <sup>2</sup> /s
Odor	charakteristisch / characteristic
Form	flüssig / liquid

### Areas of application

Suitable for use in all diesel engines, with or without turbochargers. Safe for use with catalytic converters and particulate filters (DPF).

### Application

For best results and long-term effect add DPF protector every 2.000 km (1.200 miles). Contents (250 mL) is sufficient for 50–70 Liters (14 gal. to 18 gal.) diesel.



### Available pack sizes

250 ml Can sheet metal 7703  
CANADA (-EN-F-)

**Our information is based on thorough research and may be considered reliable, although not legally binding.**