

Valve Clean

Description

Cleans valves, injection systems, intakes, carburetors, combustion chambers, and prevents deposits. This optimizes engine output and improves fuel combustion, protecting the engine under extreme loads, e.g. urban traffic, short runs and traffic jams, and reduces pollutant emissions.

Properties

- reduces deposits
- reduces residues
- good corrosion protection
- tested for turbochargers and catalytic converters
- burns ash-free
- environmentally friendly
- economical
- prevents carburetor icing

Technical data

Color / appearance	hellbraun / light brown
Density at 15 °C	0,809 g/ml DIN 51757
Flash point	+63 °C DIN ISO 2592
Pour point	< -40 °C DIN ISO 3016
Viscosity at 40 °C	<7 mm ² /s
Form	flüssig / liquid
Odor	charakteristisch / characteristic

Areas of application

For all gasoline engines (carburettor and fuel-injection engines).

Application

Add to fuel whenever filling up. One 150 ml can of Valve Cleaner is sufficient for 75 litres of fuel.



Available pack sizes

150 ml Can sheet metal	1014 D-F-NL
150 ml Can sheet metal	2503 D-E-P
150 ml Can sheet metal	2809 DK-N-S-FIN
150 ml Can sheet metal	2952 GB-GR-I
150 ml Can sheet metal	8373 GB-ARAB-F
150 ml Can sheet metal	20456 D-PL-BG
150 ml Can sheet metal	20690 D-GB-CN
150 ml Can sheet metal	21504 F-D
150 ml Can sheet metal	21621 RO-CZ-SK

Our information is based on thorough research and may be considered reliable, although not legally binding.