

Product information

PI 29/24/04/2019

Speed Tec Gasoline



Description

State-of-the-art, ash-free fuel additive for improving combustion and acceleration in partial load range. Compatible with all gasoline qualities. Improves considerably vehicle acceleration.

Properties

- improves the acceleration
- optimizes engine performance
- contains no organometallic compounds
- tested for catalytic converters
- does not influence the octane number
- better drivability

Technical data

Base	Additiv-Kombination in Trägerflüssigkeit / Additive mixture in carrier fluid
Color / appearance	hellbraun / light brown
Density at 59 °F	0,825 g/cm ³
Flash point	>145 °F
Odor	charakteristisch / characteristic
Form	flüssig / liquid
Viscosity at 104 °F	<7 mm ² /s

Available pack sizes

250 ml Can sheet metal	20234 USA (-EN-)
250 ml Can sheet metal	20340 CANADA (-EN-F-)

Our information is based on thorough research and may be considered reliable, although not legally binding.

Areas of application

Used as an additive in the fuel of all 4-stroke gasoline engines, especially for motor vehicle engines. For the improvement of vehicle acceleration and smooth operation.

Application

One 250 ml can is sufficient for up to 75 liters (20 gal.) of fuel. Can be mixed with the fuel at any time. Minimum fuel filling of 25 liters (7 gal.) is requested for optimum product performance.

Comment

 **WARNING:** Cancer- www.P65Warnings.ca.gov