

# Product information

PI 43/20/04/2021



## Speed Tec Gasoline



### Description

High-tech fuel additive, developed specifically for improved throttle response under partial engine load. Optimizes fuel atomization and combustion, cleans fuel system while providing maximum engine performance and efficiency.

### Properties

- improves the acceleration
- optimizes engine performance
- contains no organometallic compounds
- tested for the use with catalytic converters
- does not affect the octane rating
- improved driveability

### Technical data

Base	Additiv-Kombination in Trägerflüssigkeit / Additive mixture in carrier fluid
Color / appearance	hellbraun / light brown
Density at 59 °F	0,825 g/cm <sup>3</sup>
Flash point	>145 °F
Odor	charakteristisch / characteristic
Form	flüssig / liquid
Viscosity at 104 °F	<7 mm <sup>2</sup> /s

### Available pack sizes

250 ml Can sheet metal	20234 USA (-EN-)
250 ml Can sheet metal	20340 CANADA (-EN-F-)

**Our information is based on thorough research and may be considered reliable, although not legally binding.**

### Areas of application

Suitable for use in all 4- and 2-stroke gasoline engines, with or without turbochargers. Safe for use with catalytic converters and particulate filters (GPF).

### Application

Contents (250 mL) is sufficient for 25–75 Liters (7 gal. to 20 gal.) fuel. Perfect for constant use at any kind refueling. Can be mixed with the fuel at any time.

### Comment

 **WARNING:** Cancer- [www.P65Warnings.ca.gov](http://www.P65Warnings.ca.gov)