Product information

PI 10/08/03/2016

mtx Carburetor and Valve Cleaner

Description

mtx Carburettor Cleaner is a modern, ash-free combination of additives with cleaning and dispersing properties which protects the carburettor components. The product has been formulated using state-of-the-art additive and fuel technologies in accordance with the requirements of today's engines, fuels and running conditions.

Properties

- cleans carburetors
- protects fuel against oxidation and aging
- good corrosion protection
- prevents carburetor icing
- prevents residues generated by combustion process
- tested for turbochargers and catalytic converters
- reduces the risk of knocking combustion
- highly economical
- optimizes engine performance
- normalizes gasoline consumption and exhaust emissions values
- has a lasting effect
- increases operational reliability

Technical data

Base	Additiv-Kombination in Trägerflüssigkeit / additive mixture in liquid carrier
Color / appearance	hellgelb, klar / light yellow, clear
Regulation on Flammable Liquids Class (Germany)	A II
Flash point	41 °C
Pour point	- 45 °C
Form	flüssig / liquid
Odor	charakteristisch / characteristic
Viscosity at 40 °C	<7 mm²/s
Density at 15 °C	0,765 g/cm³

Areas of application

Used as an additive for the fuel of all 2-stroke and 4-stroke petrol engines, especially for motor vehicle engines. Also used for small engines for ships and industry. When decommissioning and preserving engines, add Carburettor Cleaner to the petrol at the rate of 1 %. Follow the instructions for decommissioning and preserving engines.

Application

One 300 ml can is sufficient for 70 litres of fuel. Mix the contents of the can with the fuel. Mixing takes place automatically.

Time between additions
Add to fuel every 2,000 km for long-term effect. The fuel tank should be at least half to completely full. For constant use, add to fuel at the rate of 0.3-0.5 %.

Available pack sizes

300 ml Can sheet metal	5100 D-F-NL
300 ml Can sheet metal	2123 D-E-P
300 ml Can sheet metal	2507 GB-ARAB-F
300 ml Can sheet metal	2810 DK/N-S-FIN
300 ml Can sheet metal	1818 GB-GR-I
300 ml Can sheet metal	1902 D-F-I
300 ml Can sheet metal	8339 D-PL-BG
300 ml Can sheet metal	1992 RUS-UA
300 ml Can sheet metal	2785 GB-AUS
50 l Drum sheet metal	5102 D-GB

Our information is based on thorough research and may be considered reliable, although not legally binding.

LIQUIMOLY GmbH
Jerg-Wieland-Str. 4
89081 Ulm-Lehr

Postfach 2829
89018 Ulm
Germany

Phone: +49 (0)731/1420-13
Fax: +49 (0)731/1420-82
e-mail: info@liqui-moly.de

Service-hotline: 0800/8323230
Technical hotline: +49 (0)731/1420-871
www.liqui-moly.de