

Product information

Motorbike 4T Bike-Additive

PI 30/26/11/2019



Description

Increases engine performance. Removes deposits in the fuel system, on valves, spark plugs and in the combustion chamber and prevents renewed formation. Regular use keeps fuel system in perfect condition and ensures optimal performance. Protects the entire fuel system from corrosion. Prevents carburetor icing. Cat tested.

Properties

- optimizes engine performance
- prevents corrosion in the fuel system
- reduces residues
- environmentally friendly
- tested for the use with catalytic converters
- increases operational reliability
- for carburetor and fuel-injection engines
- highly economical
- reduces the risk of knocking combustion
- normalizes fuel consumption and exhaust emissions values

Technical data

Base	Additiv-Kombination in Trägerflüssigkeit / additive mixture in liquid carrier
Color / appearance	hellgelb, klar / light yellow, clear
Regulation on Flammable Liquids Class (Germany)	A II
Flash point	>142 °F
Pour point	-49 °F
Form	flüssig / liquid
Odor	charakteristisch / characteristic
Viscosity at 104 °F	<7 mm ² /s
Density at 59 °F	0,765 g/cm ³

Areas of application

Added to fuel for all four-stroke motorbike engines (aspirated and injection).

Application

125 ml is sufficient for up to 20 liters (5.2 gal.) of gasoline fuel. Minimum fuel filling of 15 liters (4 gal.) is requested for optimum product performance. Add every time you fill up. Product is self mixing with fuel.

Comment

 **WARNING:** Cancer- www.P65Warnings.ca.gov

Available pack sizes

125 ml Can sheet metal 20048
USA (-EN-)

Our information is based on thorough research and may be considered reliable, although not legally binding.