

Product information

Motorbike 2T Bike-Additive

PI 26/29/03/2019



Description

Increases engine performance. Removes deposits in the fuel system and on intake and exhaust ports and prevents new formation. Protects the entire fuel system from corrosion. Cat tested. Clean engines need less fuel and reduce emissions.

Properties

- increases operational reliability
- tested for catalytic converters
- optimizes engine performance
- environmentally friendly
- highly economical
- prevents corrosion in the fuel system
- reduces residues
- normalizes gasoline consumption and exhaust emissions values
- cleans carburetors

Technical data

Base	Additiv-Kombination in Trägerflüssigkeit / additive mixture in liquid carrier
Color / appearance	hellgelb, klar / light yellow, clear
Regulation on Flammable Liquids Class (Germany)	A II
Flash point	>61 °C
Pour point	-45 °C
Form	flüssig / liquid
Odor	charakteristisch / characteristic
Viscosity at 40 °C	<7 mm ² /s
Density at 15 °C	0,765 g/cm ³

Areas of application

For all 2-cycle engines with mixed or separate lubrication.

Application

One filling with the dispenser (25 ml) is sufficient for 5 l fuel or fuel mixture.



Available pack sizes

250 ml Dispensing bottle plastic	1582 D-GB-I-E-P
250 ml Dispensing bottle plastic	5919 D-F-I-GR
250 ml Dispensing bottle plastic	20859 JP

Our information is based on thorough research and may be considered reliable, although not legally binding.