

Product information

Pro-Line Super Diesel Additive

PI 14/25/06/2020



Description

Pro-Line Super Diesel Additive is a combination of agents with cleansing, dispersing and material-protecting characteristics and cetane number increasing properties. The product was specially designed for use with the latest operating fluids (e.g. low-sulfur diesel fuels with portions of biodiesel). Pro-Line Super Diesel Additive can be used in all diesel engines, including those with pumped-jet and common rail injection systems. The resulting Lubricity Improver provides better lubricity for diesel fuels low in sulfur. The increase in ignition performance improves the combustion of the fuel. This, in turn, reduces exhaust emissions. A high portion of corrosion protection additives reliably protects the entire fuel system from the formation of rust and corrosion. The exceptional cleansing effect of Pro-Line Super Diesel Additive keeps components clean, prevents deposits from forming and maintains engine performance at a consistently high level.

Properties

- protects injection system components from wear
- prevents expensive repairs
- excellent cleaning effect
- increases the lubricating effect
- outstanding corrosion protection
- boosts the cetane number
- tested for the use with catalytic converters
- prevents the build-up of deposits
- prevents seizing and the injector needles from gumming up
- guarantees optimum combustion
- highly economical
- guarantees consistently good engine performance
- stable to oxidation

Technical data

Base	Additiv-Kombination in Trägerflüssigkeit / additive mixture in liquid carrier
Color / appearance	hellbraun, klar / light brown, clear
Density at 15 °C	0,842 g/cm ³
Regulation on Flammable Liquids Class (Germany)	A III
Flash point	63 °C
Pour point	- 36 °C
Form	flüssig / liquid

Technical data

Odor charakteristisch / characteristic

Areas of application

Added to diesel fuel for all diesel engines, including those with pumped-jet and common rail injection systems. Also suited for use in stationary engines.

Application

Pro-Line Super Diesel Additive can be added to the fuel after carrying out repair work on the fuel system or during an inspection. Pro-Line Super Diesel Additive can be added every 2,000 km as a preventative measure or added to commercial vehicles at every other refueling stop. Mixing takes place automatically. Contents of the can are sufficient to treat up to 300 liters of fuel (dosage 1:300). Pro-Line Super Diesel Additive is also well-suited for decommissioning vehicles by protecting the fuel system from corrosion build-up.

Available pack sizes

1 l Can sheet metal	5176 D-GB-I-E-P
1 l Can sheet metal	2801 GB-DK-FIN-N-S

Our information is based on thorough research and may be considered reliable, although not legally binding.