

# Product information

## Pro-Line Gear Oil Leak Stop

PI 19/09/09/2020



### Description

Pro-Line Gear Oil Leak Stop rejuvenates hardened seals made of rubber or plastic. Stops oil leakage in transmissions that drip. No more environmentally problematic oil patches. Prevents oil leaking onto clutches and prevents lubrication deficiency and transmission damage due to an insufficient amount of oil.

### Properties

- simple to use
- avoids oil leaking onto clutches
- miscible with all commercially available gear oils
- optimum lubrication in extreme operating conditions
- prevents oil spots and pollution of the environment

### Technical data

Viscosity at 40 °C	642 mm <sup>2</sup> /s DIN 51562
Viscosity index	101 DIN ISO 2909
Flash point	66 °C DIN ISO 2592
Pour point	-27 °C DIN ISO 3016
Color number (ASTM)	3,5 DIN ISO 2049
Base	Additivkombination / combination of additives
Color / appearance	blau / blue
Density at 20 °C	0,92 g/ml
Odor	charakteristisch / characteristic
Form	flüssig / liquid

### Areas of application

For all manual, auxiliary, and differential transmissions.

### Application

Contents of can (500 ml) sufficient to treat up to 10 liters of gear oil. The product can be added at any time. Sealing first takes place after about 600 to 800 km of driving. To guarantee a lasting effect, we recommend using Pro-Line Gear Oil Leak Stop at every oil change.

**Note: Not suitable for use in fully automatic transmissions or in transmissions with a wet clutch!**



### Available pack sizes

500 ml Can sheet metal	5199
	D-GB-I-E-P

**Our information is based on thorough research and may be considered reliable, although not legally binding.**