

Product information

Pro-Line Radiator Stop Leak K

PI 22/25/06/2020



Description

Dispersion for sealing leaks in coolant circuits in passenger cars, trucks and buses. Reliably seals hairline cracks and smaller leaks. Can also be used to prevent the need for repair work on the cooling system. The solids dispersion is stabilized in carrier fluid.

Properties

- suitable for aluminum radiators
- compatible with conventional coolant water refiners and antifreezes
- no negative side effects on the water pump or heating circuit
- permanently and reliably seals hairline cracks and small leaks
- for preventive use

Technical data

Form	flüssig / liquid
Color / appearance	weiß / white
Density at 20 °C	1,08 g/cm ³
Viscosity	35 s
Solubility in water	mischbar / mixable
Flash point	>100 °C

Areas of application

Used for sealing small leaks in water cooling circuits of passenger motor vehicles, commercial vehicles, buses, and industrial applications. Also suited for cooling circuits equipped with water filters.

Application

Shake well before use. Add contents to the cold cooling system and start up the heater. Then drive the vehicle for at least 10 minutes. Contents will treat up to 40 liters of coolant.

Comment

Store free of frost.

Contains biocides as protective agents. Contains a mixture of 5-chloro-2-methyl-2H-isothiazol-3-one [EC no. 247-500-7] and 2-methyl-2H-isothiazol-3-one [EC no. 220-239-6] (3:1).



Available pack sizes

250 ml Can sheet metal	5178
	D-GB-I-E-P
250 ml Can sheet metal	20457
	D-PL-BG

Our information is based on thorough research and may be considered reliable, although not legally binding.