

Hypoid Gear Oil (GL5) SAE 80W

Description

Hypoid Gear Oil SAE 80W is a high-performance, high-pressure gear oil manufactured from carefully selected base oils and multifunctional "extreme pressure" additives. It is suitable for powered transmission and axle drives, especially for high-load hypoid transmissions.

Properties

- reduces running noise
- does not attack common sealing materials
- excellent resistance to aging
- excellent viscosity/temperature properties
- minimizes wear
- high pressure-absorption capability

Specifications and approvals:

API GL5 • MIL-L 2105 D • ZF TE-ML 17B

LIQUI MOLY also recommends this product for vehicles or assemblies for which the following specifications or original part numbers are required:

MAN 342 Typ M1 • Volvo 97314

Technical data

SAE class (gear oils)	80W SAE J306
Density at 59 °F	0,880 g/cm ³ DIN 51757
Viscosity at 104 °F	100 mm ² /s ASTM D 7042-04
Viscosity at 212°F	11,1 mm ² /s ASTM D 7042-04
Viscosity at -15 °F (Brookfield)	<= 150000 mPas ASTM D 2983-09
Viscosity index	96 DIN ISO 2909
Pour point	-17 °F DIN ISO 3016
Flash point	421 °F DIN ISO 2592
Color number (ASTM)	3,5 DIN ISO 2049

Areas of application

For high-load motor vehicle transmissions, particularly axle drives with hypoid gearing.



Application

During selection, keep to the viscosity class stipulated by the transmission manufacturer. Miscible with all branded gear oils. Fully effective only when used alone. Only use in manual transmissions for which API GL 5 oils have been stipulated.

Available pack sizes

205 l Drum sheet metal 22057
USA AND CANADA (-EN-F-)

Our information is based on thorough research and may be considered reliable, although not legally binding.