

## Hochleistungs-Getriebeöl (GL3+) SAE 75W-80

### Description

Synthetic transmission fluid with high performance reserves. Promotes precise frictional behavior under a wide temperature range. Guarantees best wear protection and shifting performance in manual transmissions of numerous manufacturers. Suitable for extended oil service intervals.

### Properties

- reduces gearshift resistance
- extremely long oil change intervals
- outstanding corrosion protection
- excellent wear resistance
- excellent viscosity/temperature properties
- reduces transmission noise
- very compatible with seals
- high pressure-absorption capability

### Specifications and approvals:

API GL3+

### LIQUI MOLY also recommends this product for vehicles or assemblies for which the following specifications or original part numbers are required:

DAF • Eaton Extended Drain (300.000km) • IVECO • MAN 341 Typ E3 • MAN 341 Typ Z3 • Renault Trucks • Volvo 97305 • ZF TE-ML 02D • ZF TE-ML 08

### Technical data

SAE class (gear oils)	75W-80 SAE J306
Density at 59 °F	0,860 g/cm <sup>3</sup> DIN 51757
Viscosity at 104 °F	55,8 mm <sup>2</sup> /s ASTM D 7042-04
Viscosity at 212°F	9,5 mm <sup>2</sup> /s ASTM D 7042-04
Viscosity at -40 °F (Brookfield)	<= 150000 mPas ASTM D 2983-09
Viscosity index	154 DIN ISO 2909
Pour point	-44 °F DIN ISO 3016
Flash point	464 °F DIN ISO 2592
Color number (ASTM)	L 1,5 DIN ISO 2049



### Areas of application

For manual transmissions where a transmission fluid according to API GL3 classification is required.

### Application

Mixable with transmission fluids of the same classification, full product performance only when use the product pure. Observe manufacturers instructions.

### Available pack sizes

1 l Can plastic	1134 D-NL-F-GR-ARAB
1 l Can plastic	22080 USA AND CANADA (-EN-F-)

**Our information is based on thorough research and may be considered reliable, although not legally binding.**