

Top Tec ATF 1600

Description

Fully synthetic automatic transmission oil from the latest generation with extremely high performance reserves. Excellent ageing stability. Secures maximum transmission performance. Especially suitable for shifting problems. With improved formula for long transmission life. Enables extremely long oil change intervals. Color: Red.

Benefits:

- ideal viscosity/temperature properties
- best possible anti-froth protection

Properties

- excellent corrosion protection
- excellent wear resistance
- prevents foam formation
- excellent viscosity/temperature properties
- very good low-temperature properties
- outstanding resistance to oxidation
- for eliminating shifting problems
- outstanding friction characteristics
- excellent resistance to aging

Specifications and approvals:

MB-Approval 236.14

LIQUI MOLY also recommends this product for vehicles or assemblies for which the following specifications or original part numbers are required:

MB 236.12

Technical data

Density at 59 °F	0,850 g/cm ³ DIN 51757
Viscosity at 104 °F	28,7 mm ² /s ASTM D 7042-04
Viscosity at 212°F	6,45 mm ² /s ASTM D 7042-04
Viscosity at -40 °F (Brook-field)	<= 20000 mPas ASTM D 2983-09
Viscosity index	188 DIN ISO 2909
Flash point	403 °F DIN ISO 2592
Pour point	-49 °F DIN ISO 3016
Color / appearance	rot



Areas of application

Developed for the Mercedes-Benz 7-speed automatic transmission generation and is backwards compatible to all older Mercedes-Benz 5-speed automatic transmissions. Comply with the vehicle or aggregate manufacturer's instructions.

Application

The specifications and instructions from the unit or vehicle manufacturer must be followed. Optimum effectiveness is only possible when the product is used unmixed.

Available pack sizes

1 l Can plastic	20024 USA AND CANADA (-EN-F-)
20 l Canister plastic	20026 USA AND CANADA (-EN-F-)

Our information is based on thorough research and may be considered reliable, although not legally binding.