

Top Tec ATF 1200

Description

Automatic transmission fluid based on the latest generation of synthetic base oils in combination with a high-performance additive package. This fluid ensures optimum resistance against aging and excellent protection against wear. Conforms to the requirements of numerous component and vehicle manufacturers and guarantees proper operation even under extreme operating conditions.

Effect:

- automatic gear oil from the latest generation
- conforms to the requirements of numerous unit and vehicle manufacturers

Properties

- highest thermal stability
- excellent corrosion protection
- enables a multifaceted range of applications
- excellent viscosity/temperature properties
- very good low-temperature properties
- high chemical resistance
- excellent wear protection
- optimum stability to aging
- outstanding friction characteristics

Specifications and approvals:

Allison C4 • Dexron III H • Ford Mercon V • Honda ATF Z1 (except CVT) • Hyundai SP-II • Hyundai SP-III • JASO 1-A • Kia SP-II • Kia SP-III • Mazda ATF M-III • Mazda ATF M-V • Mitsubishi SP-II • Mitsubishi SP-III • Nissan AT-Matic D Fluid • Nissan AT-Matic J Fluid • Nissan AT-Matic K Fluid • Toyota Type T-II • Toyota Type T-IV

LIQUI MOLY also recommends this product for vehicles or assemblies for which the following specifications or original part numbers are required:

Allison TES 295 • BMW 7045 E • BMW 8072 B • BMW LA 2634 • BMW LT 71141 • Caterpillar TO-2 • Chrysler ATF +3 • Chrysler ATF +4 • Daimler NAG-1 • JWS 3309 (Aisin Warner) • MAN 339 Typ V1 • MAN 339 Typ Z1 • MAN 339 Typ Z2 • MB 236.2 • MB 236.3 • MB 236.5 • MB 236.6 • MB 236.7 • MB 236.9 • MB 236.10 • MB 236.11 • Subaru ATF • Voith H55.6335.XX (G 607) • Volvo 97340 • Volvo 97341 • VW G 052 162 • VW G 052 990 • VW G 055 025 • ZF TE-ML 02F • ZF TE-ML 03D • ZF TE-ML 04D • ZF TE-ML 05L • ZF TE-ML 09 • ZF TE-ML 11A • ZF TE-ML 11B • ZF TE-ML 14A • ZF TE-ML 14B • ZF TE-ML 17C



Technical data

Density at 59 °F	0,850 g/cm ³ DIN 51757
Viscosity at 104 °F	36,4 mm ² /s ASTM D 7042-04
Viscosity at 212°F	6,85 mm ² /s ASTM D 7042-04
Viscosity at -40 °F (Brookfield)	<= 20000 ASTM D 2983-09
Viscosity index	150 DIN ISO 2909
Pour point	-54 °F DIN ISO 3016
Flash point	442 °F DIN ISO 2592
Color / appearance	rot

Areas of application

For automatic transmissions, specific manual gear-boxes, power steering systems, hydraulic's and auxiliary drives in automotive and commercial vehicles. Usage according to the prescribed specifications from the unit or vehicle manufacturer.

Application

The specifications and instructions from the unit or vehicle manufacturer must be followed. Top Tec ATF 1200 may be used for refilling systems in which traditional ATF fluids are used. Optimum effectiveness, however, is only possible when the product is used on its own (i.e. no mixing).

Comment

 **WARNING: Cancer-** www.P65Warnings.ca.gov

Available pack sizes

1 l Can plastic	20018 USA AND CANADA (-EN-F-)
-----------------	----------------------------------

Product information

PI 30/19/08/2019



Top Tec ATF 1200

Available pack sizes

5 l Canister plastic	20020 USA AND CANADA (-EN- F-)
20 l Canister plastic	20022 USA AND CANADA (-EN- F-)

Our information is based on thorough research and may be considered reliable, although not legally binding.