

## Top Tec ATF 1800

### Description

Low-viscosity high-performance oil of the new generation for automatic transmissions. It is based on synthesis technology with modern, high-performance additives. Aside from excellent ageing and oxidation stability, optimal shifting is guaranteed under all operating conditions thanks to the extremely high viscosity index. It enables long oil change intervals.

### Properties

- excellent viscosity/temperature properties
- prevents foam formation
- enables a multifaceted range of applications
- outstanding friction characteristics
- high resistance to aging
- very good low-temperature properties
- excellent corrosion protection
- high wear resistance
- outstanding resistance to oxidation

### Specifications and approvals:

Dexron VI • Ford Mercon LV

### LIQUI MOLY also recommends this product for vehicles or assemblies for which the following specifications or original part numbers are required:

Aisin Warner AW-1 • BMW 83 22 0 142 516 • BMW 83 22 2 152 426 • BMW 83 22 2 289 720 • BMW 83 22 2 305 396 • BMW 83 22 2 305 397 • BMW 83 22 2 355 599 • BMW M-1375.4 • Fiat 9.55550-AV5 • JWS 3324 (Aisin Warner) • Land Rover TYK 500050 • Honda ATF 3.1 • Honda ATF DW-1 • Hyundai SP-IV • Mazda ATF FZ • MB 236.12 • MB 236.14 • Mitsubishi Dia Queen ATF-PA • Nissan AT-Matic S Fluid • Toyota WS • VW G 055 005 • VW G 055 540 • VW G 060 162

### Technical data

Density at 15 °C	0,845 g/cm <sup>3</sup> DIN 51757
Viscosity at 40 °C	28,5 mm <sup>2</sup> /s ASTM D 7042-04
Viscosity at 100 °C	5,8 mm <sup>2</sup> /s ASTM D 7042-04
Viscosity at -40°C (Brook-field)	<= 15000 mPas ASTM D 2983-09
Viscosity index	155 DIN ISO 2909
Pour point	-48 °C DIN ISO 3016



### Technical data

Flash point	210 °C DIN ISO 2592
Color / appearance	bräunlich/brownish
Color number (ASTM)	4,0 DIN ISO 2049

### Areas of application

For ZF 6HP19/21/26/28/32, ZF 8HP45/50/55/65/70/75/90/95 and ZF 9HP48 type automatic transmissions that are installed in various Audi, BMW, Honda, Jaguar, Land Rover, Porsche, etc. vehicles. Meets further specifications, allowing it to cover an even wider range of vehicles.

### Application

The specifications and instructions from the assembly or vehicle manufacturer must be followed! Optimum effectiveness is only possible when the product is used unmixed.

### Available pack sizes

1 l Can plastic	3687 D-GB-I-E-P
1 l Can plastic	9704 D-GB-F-ARAB
1 l Can plastic	20461 D-PL-H-RO-TR
1 l Can plastic	21234 ALGERIEN-GB-ARAB-F
1 l Can plastic	21107 D-GB-CN
5 l Canister plastic	20662 D-GB-I-E-P
5 l Canister plastic	21256 ALGERIEN-GB-ARAB-F
20 l Canister plastic	3688 D-GB-I-E-P
60 l Drum sheet metal	3689 D-GB

# Product information

PI 76/17/06/2020



## Top Tec ATF 1800

### Available pack sizes

205 l Drum sheet metal    20624  
D-GB

**Our information is based on thorough research and may be considered reliable, although not legally binding.**