

# Product information

## Motorbike Gear Oil 75W-90

PI 36/27/08/2020



### Description

High-performance high-pressure transmission oil made from high-grade synthetic base oils and additives. Facilitates smooth and precise shifting even under extreme conditions and complies with performance class API GL5. Has excellent wear protection properties and ideal viscosity-temperature behavior.

### Properties

- high efficiency
- excellent wear protection
- wide viscosity range
- reduces transmission noise
- good corrosion protection
- guarantees smooth gearshifting
- guarantees low fuel consumption

### Specifications and approvals:

API GL5 • MIL-L 2105 C • MIL-L 2105 D

### Technical data

SAE class (gear oils)	75W-90 SAE J306
Density at 15 °C	0,855 g/cm <sup>3</sup> DIN 51757
Viscosity at 40 °C	80,9 mm <sup>2</sup> /s ASTM D 7042-04
Viscosity at 100 °C	14,3 mm <sup>2</sup> /s ASTM D 7042-04
Viscosity at -40°C (Brookfield)	<= 150000 mPas ASTM D 2983-09
Viscosity index	184 DIN ISO 2909
Pour point	-60 °C DIN ISO 3016
Flash point	190 °C DIN ISO 2592
Color number (ASTM)	L 1,0 DIN ISO 2049

### Areas of application

For the most extremely stressed motorcycle transmission and final drives. Comply with the transmission manufacturer's instructions.

### Application

As stipulated for gear oil. The transmission manufacturer's instructions must be followed. Miscible with mineral-base oil residues which can remain during oil changes in transmissions and drives. Can be easily

disposed of with standard used oil. Optimum effect only when used alone.

### Available pack sizes

500 ml Can plastic	1516 D-GB-I-E-P
500 ml Can plastic	5925 D-F-I-GR
1 l Can plastic	3825 D-GB-I-E-P
20 l Canister plastic	3826 D-GB
60 l Drum sheet metal	3827 D-GB

**Our information is based on thorough research and may be considered reliable, although not legally binding.**

