

## Motorbike Gear Oil SAE 75W-90

### Description

Stipulated especially for manual transmissions and universal-shaft drives for an API-GL5. For light gear change and extreme demands. Very good wear protection properties. For year round use. With energy-conserving properties to reduce fuel consumption.

### Properties

- high efficiency
- excellent wear protection
- wide viscosity range
- reduces transmission noise
- good corrosion protection
- guarantees easy gear changing
- guarantees low fuel consumption

### Specifications and approvals:

API GL5 • MIL-L 2105 C • MIL-L 2105 D

### Technical data

SAE class (gear oils)	75W-90 SAE J306
Density at 59 °F	0,855 g/cm <sup>3</sup> DIN 51757
Viscosity at 104 °F	80,9 mm <sup>2</sup> /s ASTM D 7042-04
Viscosity at 212°F	14,3 mm <sup>2</sup> /s ASTM D 7042-04
Viscosity at -40 °F (Brookfield)	<= 150000 mPas ASTM D 2983-09
Viscosity index	184 DIN ISO 2909
Pour point	-76 °F DIN ISO 3016
Flash point	374 °F DIN ISO 2592
Color number (ASTM)	L 1,0 DIN ISO 2049

### Areas of application

For the most extremely stressed motorcycle transmission and final drives. Comply with the transmission manufacturer's instructions.

### Application

As stipulated for gear oil. The transmission manufacturer's instructions must be followed. Miscible with mineral-base oil residues which can remain during oil changes in transmissions and drives. Can be easily disposed of with standard used oil. Optimum effect

only when used alone.

### Comment

 **WARNING:** Cancer- [www.P65Warnings.ca.gov](http://www.P65Warnings.ca.gov)

### Available pack sizes

1 l Can plastic

20086

USA AND CANADA (-EN-F-)



**Our information is based on thorough research and may be considered reliable, although not legally binding.**