

Motorbike Gear Oil SAE 75W-90

Description

Fully Synthetic, GL5 high-performance extreme-pressure gear oil. Facilitates smooth and precise shifting even in extreme conditions, provides excellent wear protection properties and ideal viscosity-temperature behavior.

Properties

- high efficiency
- excellent wear protection
- wide viscosity range
- reduces transmission noise
- good corrosion protection
- gear changes are made easier
- guarantees low fuel consumption

Specifications and approvals:

API GL5 • MIL-L 2105 C • MIL-L 2105 D

Technical data

SAE class (gear oils)	75W-90 SAE J306
Density at 59 °F	0,855 g/cm ³ DIN 51757
Viscosity at 104 °F	80,9 mm ² /s ASTM D 7042-04
Viscosity at 212°F	14,3 mm ² /s ASTM D 7042-04
Viscosity at -40 °F (Brookfield)	<= 150000 mPas ASTM D 2983-09
Viscosity index	184 DIN ISO 2909
Pour point	-76 °F DIN ISO 3016
Flash point	374 °F DIN ISO 2592
Color number (ASTM)	L 1,0 DIN ISO 2049

Areas of application

Universal use in motorbike transmissions and final drives where a gear oil according to current product specifications is required or recommended.

Application

Observe the manufacturers instructions! Optimum effectiveness only when the product is used undiluted.

Comment

 **WARNING:** Cancer- www.P65Warnings.ca.gov



Available pack sizes

1 l Can plastic

20086

USA AND CANADA (-EN-F-)

Our information is based on thorough research and may be considered reliable, although not legally binding.