

## Motorbike HD-Classic SAE 50 Street

### Description

Motorbike HD Classic SAE 50 is a high-performance engine oil which is formulated according to the latest technology. Selected base oils and a high additive content guarantee optimum lubrication under extreme running conditions.

### Properties

- very good dispersion properties
- high wear resistance
- excellent cleaning effect
- high shear stability
- optimum stability to aging
- guarantees low oil consumption
- low evaporation loss
- oil film strength
- miscible with all commercially available motor oils

### Specifications and approvals:

API SG

### Technical data

SAE class (engine oils)	50 SAE J300
Density at 15 °C	0,900 g/cm <sup>3</sup> DIN 51757
Viscosity at 40 °C	225 mm <sup>2</sup> /s ASTM D 7042-04
Viscosity at 100 °C	20,2 mm <sup>2</sup> /s ASTM D 7042-04
Viscosity index	104 DIN ISO 2909
Pour point	-9 °C DIN ISO 3016
Evaporation loss (Noack)	4,0 % CEC-L-40-A-93
Flash point	250 °C DIN ISO 2592
Total base number	11,0 mg KOH/g DIN ISO 3771
Sulfate ash	1,2 g/100g DIN 51575
Color number (ASTM)	L 4,5 DIN ISO 2049

### Areas of application

Four-stroke motorbike engines - especially Harley-Davidson.



### Application

The operating instructions of the engine manufacturer must be followed.

### Available pack sizes

1 l Canister plastic	1572 BOOKLET
4 l Canister plastic	1230 BOOKLET

**Our information is based on thorough research and may be considered reliable, although not legally binding.**