

## Motorbike HD-Classic SAE 50 Street

### Description

Single-grade motor oil. For use in classic motor-cycles. Especially suitable for Harley Davidson. High wear resistance and outstanding corrosion protection. Absolute shear stability. Provides quiet engine running and long engine life. Low volatile loss and oil consumption.

### Properties

- very good dispersion properties
- high wear resistance
- excellent cleaning effect
- high shear stability
- optimum stability to aging
- guarantees low oil consumption
- low evaporation loss
- oil film strength
- miscible with all commercially available motor oils

### Specifications and approvals:

API SG

### Technical data

SAE class (engine oils)	50 SAE J300
Density at 59 °F	0,900 g/cm <sup>3</sup> DIN 51757
Viscosity at 104 °F	225 mm <sup>2</sup> /s ASTM D 7042-04
Viscosity at 212°F	20,2 mm <sup>2</sup> /s ASTM D 7042-04
Viscosity index	104 DIN ISO 2909
Pour point	16 °F DIN ISO 3016
Evaporation loss (Noack)	4,0 % CEC-L-40-A-93
Flash point	482 °F DIN ISO 2592
Total base number	11,0 mg KOH/g DIN ISO 3771
Sulfate ash	1,2 g/100g DIN 51575
Color number (ASTM)	L 4,5 DIN ISO 2049

### Areas of application

Four-stroke motorbike engines - especially Harley-Davidson.



### Application

The operating instructions of the engine manufacturer must be followed.

### Available pack sizes

1 l Canister plastic	20104 USA AND CANADA (-EN-F-)
4 l Canister plastic	20106 USA AND CANADA (-EN-F-)

**Our information is based on thorough research and may be considered reliable, although not legally binding.**