

Product information

Top Tec Truck 4450 15W-40

PI 55/14/10/2020



Description

In the class of standard engine oils, Top Tec Truck 4450 is among the high performance lubricants. Due to the new additive technology with improved wear protection characteristics and oxidation stability, this lubricant meets the requirements of state-of-the-art engine concepts. In addition, the ash-reduced formulation enables an improved compatibility with catalytic converters and diesel particle filters (DPF). The chosen viscosity provides excellent protection for the engine, even in extreme situations such as under high thermal and mechanical loads. Protects the exhaust after-treatment system.

Properties

- excellent wear protection
- outstanding detergent and dispersant properties
- outstanding oil film strength
- tested for the use with catalytic converters
- ensures a long service life
- suitable for diesel particulate filters
- outstanding resistance to oxidation
- low sulfate ash, phosphorous and sulfur content (low SAPS)
- keeps the charge air cooler extremely clean

Specifications and approvals:

ACEA E9 • API CK-4 • API SN • Detroit Diesel DFS 93K222 • Ford WSS-M2C 171-F1 • Mack EOS-4.5 • MB-Approval 228.31 • Renault Trucks RLD-3 • Volvo VDS-4.5

LIQUI MOLY also recommends this product for vehicles or assemblies for which the following specifications or original part numbers are required:

ACEA E7 • Caterpillar ECF-3 • Cummins CES 20086 • Deutz DQC III-10 LA • JASO DH-2 • MAN M 3575 • MTU Typ 2.1

Technical data

SAE class (engine oils)	15W-40 SAE J300
Density at 15 °C	0,875 g/cm ³ DIN 51757
Viscosity at 40 °C	118,0 mm ² /s ASTM D 7042-04
Viscosity at 100 °C	15,4 mm ² /s ASTM D 7042-04
Viscosity at -25°C (MRV)	< 60000 mPas ASTM D4684



Technical data

Viscosity at -20°C (CCS)	<= 7000 mPas ASTM D5293
Viscosity index	135 DIN ISO 2909
HTHS at 150°C	>= 3,5 mPas ASTM D5481
Pour point	-33 °C DIN ISO 3016
Evaporation loss (Noack)	10,3 % CEC-L-40-A-93
Flash point	230 °C DIN ISO 2592
Total base number	10,5 mg KOH/g DIN ISO 3771
Sulfate ash	<= 1,0 g/100g DIN 51575
Color number (ASTM)	L 3,5 DIN ISO 2049

Areas of application

Meets the requirements of state-of-the-art, low-emission engine concepts. Ideal for trucks, short- and long-distance buses, as well as for forestry, agricultural, and construction machinery. Due to its good performance, this product is ideally suitable for use in state-of-the-art engines according to Euro IV, V and VI emission standards. Recommended for use in vehicles with diesel particle filter (DPF). Top Tec Truck 4450 15W-40 can be used in many vehicles without any limitations and is backwards compatible. Can be used in engines of older Euro II and III emission standards, if manufacturers' specifications are observed.

Application

The operating regulations of the commercial motor vehicle and engine manufacturers must be followed for normal and extended oil change intervals. Recommended usage is for diesel engines only.

Product information

PI 55/14/10/2020



Top Tec Truck 4450 15W-40

Available pack sizes

20 l Canister plastic	3778
	D-GB-I-E-P
60 l Drum sheet metal	3779
	D-GB
205 l Drum sheet metal	3780
	D-GB
1000 l Container	3717
	D-GB

Our information is based on thorough research and may be considered reliable, although not legally binding.