

Super HD 15W-40

Description

Super HD 15W-40 is a year-round engine oil for gasoline engines and diesel engines. Selected base oils and a high additive content guarantee optimum lubrication under all running conditions and for long periods between oil changes.

Properties

- good cleaning action
- miscible with all commercially available motor oils
- tested for catalytic converters
- very good dispersion properties
- high shear stability
- optimum stability to aging
- increases the lubricating effect
- can be used in gasoline and diesel engines with and without turbocharger

Specifications and approvals:

API CD • API SF

Technical data

SAE class (engine oils)	15W-40 SAE J300
Density at 15 °C	0,875 g/cm ³ DIN 51757
Viscosity at 40 °C	109 mm ² /s ASTM D 7042-04
Viscosity at 100 °C	14,3 mm ² /s ASTM D 7042-04
Viscosity at -25°C (MRV)	< 60000 mPas ASTM D4684
Viscosity at -20°C (CCS)	< 7000 mPas ASTM D5293
Viscosity index	133 DIN ISO 2909
HTHS at 150°C	> 3,7 mPas ASTM D5481
Pour point	-30 °C DIN ISO 3016
Evaporation loss (Noack)	13,0 % CEC-L-40-A-93
Flash point	230 °C DIN ISO 2592
Total base number	6,5 mg KOH/g DIN ISO 3771
Sulfate ash	0,65 g/100g DIN 51575



Technical data

Color number (ASTM)	4,0
	DIN ISO 2049

Areas of application

Motor oil for gasoline, diesel engines.

Application

The operating instructions of the vehicle and engine manufacturers must be followed.

Available pack sizes

5 l Canister plastic	1899 D-RUS-PL-H-RO-BIH- HR-SCG
20 l Canister plastic	1896 D-GB
205 l Drum sheet metal	1898 D-GB

Our information is based on thorough research and may be considered reliable, although not legally binding.