# **Product information**

# Special Tec F ECO 5W-20



## **Description**

Low-friction motor oil based on synthetic technology. Specially developed for the requirements of Ford gasoline engines. Reliably prevents the formation of deposits, ensures excellent lubrication reliability and enables high fuel savings. In terms of the wear resistance, the requirements of the older Ford standard WSS-M2C913-C are met and, in certain points, even exceeded.

# LIQUIMOLY SPECAL TEC

### **Technical data**

Color number (ASTM) L 2,5 DIN ISO 2049

### Areas of application

For Ford gasoline engines except Ford Ka (08/2008-), Focus ST and Focus RS (2004.75 with 2.5 l Duratec-ST (VI5) engine). A lubricant from this specification is prescribed for EcoBoost engines. This motor oil is fully compatible with older versions. Ford also recommends this specification of oil for gasoline engines in which the standards WSS-M2C913-B, WSS-M2C913-C or WSS-M2C925-B are currently prescribed.

# Application

The specifications and instructions from the assembly or vehicle manufacturer must be followed!

### Available pack sizes

1 l Canister plastic 3840 D-GB-I-E-P 1 l Canister plastic 21241 ALGERIEN-GB-ARAB-F 5 l Canister plastic D-GB-I-E-P 5 l Canister plastic 21231 ALGERIEN-GB-ARAB-F 20 l Canister plastic 3842 D-GB-I-E-P 60 l Drum sheet metal 3843 D-GB 205 l Drum sheet metal 3844

Our information is based on thorough research and may be considered reliable, although not legally binding.

D-GB

# **Properties**

- high resistance to aging
- instant lubrication after cold start
- outstanding lubrication reliability
- tested for the use with catalytic converters
- outstanding engine cleanliness
- highest fuel economy
- stable to oxidation

## Specifications and approvals:

ACEA C5 • API SN • Ford WSS-M2C 948-B • Jaguar / Land Rover STJLR.03.5004

#### **Technical data**

SAE class (engine oils) 5W-20 **SAE J 300** Density at 15 °C 0,850 g/cm<sup>3</sup> DIN 51757 Viscosity at 40 °C 42,0 mm<sup>2</sup>/s ASTM D 7042-04  $8.00 \text{ mm}^2/\text{s}$ Viscosity at 100 °C ASTM D 7042-04 Viscosity at -35 °C (MRV) < 60000 mPas **ASTM D4684** Viscosity at -30°C (CCS) < 6600 mPas **ASTM D5293** 

Viscosity index 165 DIN ISO 2909 HTHS at 150°C ≥ 2,6 mPas

ASTM D5481

Pour point -39 °C DIN ISO 3016

Flash point 220 °C DIN ISO 2592

Evaporation loss (Noack) 12,0 %

CEC-L-40-A-93

Total base number 8,0 mg KOH/g

DIN ISO 3771

Sulfate ash ≤ 0,8 g/100g DIN 51575

LIQUI MOLY GmbH Jerg-Wieland-Str. 4 89081 Ulm-Lehr Postfach 2829 89018 Ulm Germany Phone: +49 (0)731/1420-0 Fax: +49 (0)731/1420-82 e-mail: info@liqui-moly.de Service-hotline: 0800/8323230 Technical hotline: +49 (0)731/1420-871 www.liqui-moly.de