

Lawnmower Oil SAE 30

Description

Single-application engine oil with state-of-the-art formulation and technology. Selected base oils with a naturally high viscosity index and a high additive content guarantee optimum lubrication under all running conditions.

Properties

- low evaporation loss
- miscible with all commercially available motor oils
- high wear resistance
- tested for catalytic converters
- excellent cleaning effect
- very good dispersion properties
- high resistance to aging
- outstanding lubricating action

Specifications and approvals:

API SJ

Technical data

SAE class (engine oils)	30 SAE J300
Density at 15 °C	0,875 g/cm ³ DIN 51757
Viscosity at 40 °C	102 mm ² /s ASTM D 7042-04
Viscosity at 100 °C	11,9 mm ² /s ASTM D 7042-04
Viscosity index	106 DIN ISO 2909
Pour point	-21 °C DIN ISO 2592
Evaporation loss (Noack)	6,8 % ASTM D 5800-08 Method B
Flash point	238 °C DIN ISO 3016
Total base number	11,0 mg KOH/g DIN ISO 3771
Sulfate ash	1,2 g/100g DIN 51575
Color number (ASTM)	4,0 DIN ISO 2049

Areas of application

Especially for 4-cycle lawnmower engines and other engines that require single grade, viscosity grade SAE 30 oil and these specifications.



Application

The operating materials instructions of the motor vehicle and engine manufacturer must be followed.

Available pack sizes

600 ml Canister plastic	1268 D
1 l Canister plastic	1264 D
5 l Canister plastic	1266 D

Our information is based on thorough research and may be considered reliable, although not legally binding.