

Lawnmower Oil SAE 30

Description

Single-grade motor oil with high-quality base oils and high additive content. Ensures first-class lubrication, optimum engine cleanliness, outstanding wear protection and a long service life of the lawnmower engine. Also provides reliable protection against corrosion under adverse conditions and when overwintering. Tested on engines with catalytic converters.

Properties

- low evaporation loss
- miscible with all commercially available motor oils
- high wear resistance
- tested for the use with catalytic converters
- excellent cleaning effect
- very good dispersion properties
- high resistance to aging
- outstanding lubricating action

Specifications and approvals:

API SJ

Technical data

SAE class (engine oils)	30 SAE J300
Density at 15 °C	0,875 g/cm ³ DIN 51757
Viscosity at 40 °C	90,0 mm ² /s ASTM D 7042-04
Viscosity at 100 °C	11,6 mm ² /s ASTM D 7042-04
Viscosity index	115 DIN ISO 2909
Pour point	-33 °C DIN ISO 2592
Evaporation loss (Noack)	6,8 % ASTM D 5800-08 Method B
Flash point	230 °C DIN ISO 3016
Total base number	11,0 mg KOH/g DIN ISO 3771
Sulfate ash	1,2 g/100g DIN 51575
Color number (ASTM)	4,0 DIN ISO 2049



Areas of application

For 4-stroke lawnmower engines and other engines that require a single-grade motor oil with viscosity class SAE 30 and the existing specifications.

Application

The specifications and instructions from the assembly or equipment manufacturer must be followed.

Available pack sizes

600 ml Canister plastic	1268 D
1 l Canister plastic	1264 D
5 l Canister plastic	1266 D

Our information is based on thorough research and may be considered reliable, although not legally binding.