

## Universal Oil for Garden Equipment 10W-30

### Description

Modern multigrade motor oils for year-round use. It exceeds the requirements set by renowned engine manufacturers such as Briggs & Stratton, Honda, Tecumseh etc. Selected base oils and a higher additive content guarantee optimum engine cleanliness as well as an outstanding lubricating effect, even under difficult operating conditions.

### Properties

- high wear resistance
- can be used in gasoline and diesel engines with and without turbocharger
- miscible with all commercially available motor oils
- tested for catalytic converters
- low evaporation loss
- very good dispersion properties
- high resistance to aging
- excellent cleaning effect
- increases the lubricating effect
- universal application

### Specifications and approvals:

ACEA A3 • ACEA B3 • API CF • API SG • API SH • API SJ

### Technical data

SAE class (engine oils)	10W-30 SAE J300
Density at 15 °C	0,860 g/cm <sup>3</sup> DIN 51757
Viscosity at 40 °C	72,0 mm <sup>2</sup> /s ASTM D 7042-04
Viscosity at 100 °C	11,6 mm <sup>2</sup> /s ASTM D 7042-04
Viscosity at -30°C (MRV)	> 60000 mPas ASTM D 4684
Viscosity at -25°C (CCS)	<= 7000 mPas ASTM D 5293
Viscosity index	156 DIN ISO 2909
Pour point	-36 °C DIN ISO 3016
Evaporation loss (Noack)	14,5 % CEC-L-40-A-93
Flash point	220 °C DIN ISO 2592
Total base number	8,3 mg KOH/g DIN ISO 3771



### Technical data

Sulfate ash	0,9 - 1,5 g/100g DIN 51575
Color number (ASTM)	L 4,0 DIN ISO 2049

### Areas of application

For 4-stroke engines, such as lawnmowers, emergency power units, riding mowers, chippers, rotary tillers, scarifiers, string trimmers, high-pressure cleaners, snow blowers, etc.

### Application

The operating regulations of the engine and tool manufacturers must be followed.

### Available pack sizes

1 l Canister plastic	1273 D
600 ml Canister plastic	7686 D

**Our information is based on thorough research and may be considered reliable, although not legally binding.**