

Saw Chain Oil 100

Description

Mineral high-performance oil formulated from selected base oils for once-through loss lubrication of chains in motor saws and reciprocating saws, etc. Outstanding adhesive properties and optimum lubricating property ensure that all moving parts such as chain links and joints have the optimum lubrication and are protected from wear. The product's favorable viscosity/temperature properties guarantee year-round reliable use at both high and low outside temperatures.

Properties

- outstanding lubricating action
- outstandingly adherent
- excellent low temperature behavior
- excellent viscosity/temperature properties

Technical data

ISO viscosity class	100 DIN 51519
Density at 15 °C	0,870 g/cm ³ DIN 51757
Viscosity at 40 °C	100 mm ² /s ASTM D 7042-04
Viscosity at 100 °C	13,2 mm ² /s ASTM D 7042-04
Viscosity index	130 DIN ISO 2909
Pour point	-39 °C DIN ISO 3016
Flash point	220 °C DIN ISO 2592
Oxide ash	0,5 g/100g DIN EN ISO 6245
Color / appearance	grau-schwarz

Areas of application

For lubricating chains of all high-performance motor saws and reciprocating saws under extreme conditions such as sawing hardwoods.

Application

For lubricating chains of all high-performance motor saws and reciprocating saws under extreme conditions such as sawing hardwoods.



Available pack sizes

1 l Canister plastic	1277 D
5 l Canister plastic	1278 D
5 l Canister plastic	2992 D-DK-FIN-N-S
20 l Canister plastic	1190 D-GB
60 l Drum sheet metal	1191 D-GB

Our information is based on thorough research and may be considered reliable, although not legally binding.