

Battery Clamp Grease

Description

Battery Clamp Grease is a special grease which is compatible with plastics and is formulated for the maintenance and care of motor vehicle electronic systems, particularly the battery terminals and electrical connectors.

Properties

- prevents leakage currents
- reduces contact resistance
- good corrosion protection
- very compatible with plastics
- good electronic properties

Technical data

Brief description	K2G-30 DIN 51502
NLGI number	2 DIN 51818
Color / appearance	rot / red
Worked penetration	265-295 1/10 mm DIN ISO 2137
Dropping point	293 °F DIN ISO 2176
Oil separation after 7 days at 104 °F	3,6 % DIN 51817
Oil separation after 18 hours at 104 °F	1,1 % DIN 51817
Flow pressure at -22 °F	<1400 mbar DIN 51805
Emcor corrosion class	0/0 DIN 51802
Copper corrosion after 24 hours at 212 °F	1 a DIN 51811
Behavior in the presence of water	0-40 DIN 51807 Teil 1
Base oil	
Viscosity at 104 °F	32 mm ² /s ASTM D 7042-04
Flash point	392 °F DIN ISO 2592
Pour point	-6 °F DIN ISO 3016
Density	0,894 g/cm ³



Application

Clean contaminated components and treat with Battery Clamp Grease.

Available pack sizes

50 g Tube plastic	20244 USA (-EN-)
-------------------	---------------------

Our information is based on thorough research and may be considered reliable, although not legally binding.

Areas of application

Used especially for battery terminals, connections and plug connectors in vehicle electronic system.