

Product information

Truck Axle Grease KP2N-30

PI 24/19/02/2019



Description

High performance lithium complex grease, which was specially developed for the high requirements of axle-bearings in commercial vehicles and buses in normal and high temperature ranges. The blue colour visually indicates the special performance of the high-tech lubricant.

Properties

- multifunctional uses
- broad operating temperature range
- optimum lubrication under all operating conditions
- increases service life
- optimum stability to aging
- highest load-carrying capacity

Technical data

Brief description	KP2N-30 DIN 51502
NLGI number	2 DIN 51818
Worked penetration	265-295 1/10 mm DIN ISO 2137
Dropping point	>260 °C DIN ISO 2176
Oil separation after 7 days at 40 °C	2,7 % DIN 51817
Oil separation after 18 hours at 40 °C	0,8 % DIN 51817
Flow pressure at -30 °C	<1400 mbar DIN 51805
Emcor corrosion class	0/0 DIN 51802
Copper corrosion after 24 hours at 100 °C	1 b DIN 51811
Behavior in the presence of water	1-90 DIN 51807 Teil 1
Four-ball tester material load/weld force	2800/3000 N DIN 51350 Teil 4
Four-ball tester wear/indentation diameter	0,60 mm DIN 51350 Teil 5
Base oil	
Viscosity at 40 °C	210 mm ² /s ASTM D 7042-04
Flash point	246 °C DIN ISO 2592
Pour point	-24 °C DIN ISO 3016

Areas of application

For long-term lubrication of roller bearings, gear hubs, wheel bearings, especially in commercial motor vehicle axles as well as in BPW aggregates. LIQUI MOLY recommends this grease as an alternative to BPW grease.

Comment

Full performance is guaranteed only when used unmixed.

Available pack sizes

400 g Lube-Shuttle	3303 D-GB-I-E-P
--------------------	--------------------

Our information is based on thorough research and may be considered reliable, although not legally binding.