

Viscous Grease ZS KOOK-40

Description

Lithium soap grease, made from carefully selected raw materials and additives. Its ideal lubricity, water resistance, adhesiveness and high-pressure resistance makes it outstanding. Designation acc DIN 51502 K00 K-40.

Properties

- excellent adhesion
- good water resistance
- minimizes wear
- outstanding lubricating action

Technical data

| | |
|---|---|
| Brief description | K00/000K-40 DIN 51502 |
| NLGI number | 00/000 DIN 51818 |
| Worked penetration | 400-460 1/10 mm DIN ISO 2137 |
| Dropping point | 165 °C DIN ISO 2176 |
| Flow pressure at -40 °C | <1400 mbar DIN 51805 |
| Emcor corrosion class | 0/0 DIN 51802 |
| Copper corrosion after 24 hours at 100 °C | 1 b DIN 51811 |
| Behavior in the presence of water | 1-90 DIN 51807 Teil 1 |
| Base oil | |
| Viscosity at 40 °C | 45 mm ² /s ASTM D 7042-04 |
| Flash point | 184 °C DIN ISO 2592 |
| Pour point | -36 °C DIN ISO 3016 |

Areas of application

Especially suited for truck central lubrication systems. As normal in viscous greases, comply with the transmission and bearing manufacturers' operating instructions.

Application

Use as usual for flow greases. The operating instructions of the transmission and bearing manufacturers must be followed.



Available pack sizes

| | |
|----------------------|--------------|
| 5 kg Bucket plastic | 4714 D-GB |
| 25 kg Bucket plastic | 4715 D-GB |

Our information is based on thorough research and may be considered reliable, although not legally binding.