

Tire Fitting Paste white

Description

Waxy fitting aid with special soap components. Formulated to aid the economic and efficient fitting of passenger car, truck and motorcycle tires.

Properties

- keeps the tire bead supple
- counteracts rust formation
- prevents the tire from sticking to the rim
- facilitates fitting/removal
- quick drying
- simple to use
- high capacity
- good gliding properties
- absolutely skin tolerant
- suitable for run-flat tires
- suitable for tire pressure monitoring system TPMS
- can be used in the newest tire generations
- biologically degradable
- silicone-free
- free of volatile organic compounds
- AOX-free

Technical data

Base	DEG, Seife / DEG soap
Color / appearance	weiß, hellgelb / white, light yellow
Density	~ 1 g/cm ³
pH value	~ 8
Form	cremig, fest / creamy, solid
Flash point	~ 240 °C
Solubility in water	löslich / soluble
Odor	schwach, geruchlos / weak, odourless
Processing temperature	schwach, geruchslos / weak, odourless
Shelf life	60 months

Areas of application

For fitting all standard wheel/tire combinations. Especially suitable for run-flat tires.

Application

Apply thinly and evenly with a brush or sponge onto the tire bead. On truck and EM tires, also paint the rim base and bead seat ring. This helps the tire to slide easily onto the rim without damage. Ensures the correct technical seat of the tire on the rim, which is a requirement for precise balancing and makes it easi-



er to remove the tire later. Note the tire manufacturer's instructions.

Available pack sizes

5 kg Bucket plastic	3021
	D-GB-I-E-P

Our information is based on thorough research and may be considered reliable, although not legally binding.