

Product information

Brake Anti-Squeal Paste

PI 22/15/06/2018



Description

Brake Anti-Squeal Paste has been specially developed from synthetic and ceramic materials which eliminate brake squeals arising between the brake piston or contact surface and the brake lining.

Properties

- good corrosion protection
- easy to use
- eliminates squeaks
- resistant to road salt and splash water
- extremely low friction
- outstanding thermal stability
- outstandingly adherent
- ideally suited as a separating paste

Technical data

Form	pastös, flüssig / pastelike, liquid
Color / appearance	blau / blue
Base	synthetische u. keramische Wirkstoffe
Density	1,08 g/ml
Operating temperature range	-40 bis +200 kurzfristig bis +250 / -40 to +200 short term +250 °C als Schmierpaste / as lubricating agent -40 bis +1200 / -40 to +1200 °C als Trennpaste / as release agent
Flash point	>210 °C
Odor	schwach / slightly
Shelf life in original sealed container	36 months

Areas of application

Brake Anti-Squeal Paste has been specially developed for the assembly, repair and maintenance of brake systems. Used for basic lubrication and as a preventive measure against brake squeals. However, it is also universally suitable for numerous applications apart from brake systems.

Application

With floating brake callipers, first clean all sliding surfaces, channels and contact surfaces using a brush or brake file. Next, clean the brake components with Rapid Cleaner (Part no. 3318). After the solvent has evaporated, coat cleaned parts with Brake

Anti-Squeal Paste on all sliding surfaces, channels and contact surfaces.

Comment

Do not under any circumstances allow Brake Anti-Squeal Paste to get onto the friction surface of the brake lining or the brake disc.

Available pack sizes

10 g Cushion plastic	3078 D
10 g Cushion plastic	7585 RUS-UA
10 g Cushion plastic	21121 GB
100 g Tube plastic	3077 D-GB-I-E-P
1 kg Can sheet metal	3084 D-GB-I-E-P

Our information is based on thorough research and may be considered reliable, although not legally binding.