

Product information

Exhaust Assembly Paste

PI 22/10/06/2020



Description

Exhaust Assembly Paste has been developed for quick, simple, gas-tight assembly of pipe and flange connections on exhaust systems. Exhaust Assembly Paste does not contain asbestos, does not pollute the environment, is permanently heat resistant and allows dismantling without destruction.

Properties

- does not contain asbestos
- simple to use
- high gas tightness
- simple to use without disassembly
- outstanding thermal resistance

Technical data

Base	Natronwasserglas / sodium waterglass
Form	pastös / pastelike
Density	~ 1,71 g/cm ³
Thermal stability	~ 700 °C
Shelf life	2 Jahre im gut verschlossenen Originalgebinde bei kühler und frostfreier Lagerung / 2 years in its original container, well sealed, in a cool area free of frost
Color / appearance	grau / grey
Odor	geruchslos / odourless

Areas of application

For gas-tight installation of exhaust systems, tailpipe trim, screw and plug connections and flame rings.

Application

The exhaust components to be connected must be free of rust, grease and dust. Apply the paste generously and push the parts together. If necessary, make the paste more pliable using water. The paste is hardened by the heat from the exhaust.



Available pack sizes

150 g Tube plastic	3342 D-GB-I-E-P
150 g Can sheet metal	2835 GB-DK-FIN-N-S

Our information is based on thorough research and may be considered reliable, although not legally binding.