

PTFE Powder Spray

Description

PTFE Powder Spray is a grease-free lubricant and re-release agent based on PTFE (Teflon or polytetrafluorethylene). With its long-term lubricating action, this product has universal application particularly in work areas where oil or silicone-based agents cannot be used because they ruin finishing work such as painting or because of other reasons.

Properties

- easy to use
- silicone-free
- no taste
- low coefficient of friction
- high chemical resistance
- eliminates squeaks
- suitable for care, protection and insulation
- outstanding thermal stability

Technical data

Color / appearance	weiß / white
Base	PTFE
Density	0,58 g/ml
Operating temperature range	-40 bis +250 / -40 to +250 °C
Propellant	Propan, Butan / propane, butane
Flash point	-60 °C
Form	flüssig / liquid
Odor	charakteristisch/ characteristic

Areas of application

PTFE Powder Spray is a lubricant which can be used on practically any material. In automotive engineering, it is the optimum lubricant for belt mechanisms and guide rails such as those found under seats. It can also be used as a lubricant and separating agent for eliminating any type of noise from covers and seats etc. In industry it is used particularly in processing textiles and wood for bearings, slip rails, rollers, chains and threads. It also has universal application in the household. Ideally suitable as a re-release agent in plastics processing.

Application

Spray PTFE Powder Spray thinly and uniformly onto the clean and grease-free surface. If greater layer thickness is required, the preceding coat must be allowed to dry before applying another coat.

After use, clear spray nozzle by inverting can and

spraying until only the propellant emerges.

Available pack sizes

400 ml Can aerosol	3076 D-GB-I-E-P
400 ml Can aerosol	2871 GB-DK-FIN-N-S

Our information is based on thorough research and may be considered reliable, although not legally binding.

