

Electronic Spray

Description

Fully synthetic, silicone free contact spray, formulated for use on vehicle electronic and general electrical systems. Reduces fretting and corrosion, suppresses moisture. It is neutral to paints, common plastics and rubber. Cleans and protects electrical connectors.

Properties

- cleans contaminated contacts
- good water separation
- good corrosion protection
- penetrates layers of oxides and sulphides
- drives out moisture
- reduces contact resistance
- silicone-free

Technical data

Color / appearance	blau / blue
Base	Syntheseöl / synthetic oil
Viscosity at 104 °F	49,5 mm ² /s
Viscosity at 212°F	7 mm ² /s
Viscosity index	145
Pour point	-63 °F DIN ISO 3016
Flash point	394 °F DIN ISO 2592
Evaporation loss (Noack)	2,1 Gew.-% DIN ISO 2909
Water content	40 ppm $\Omega \cdot \text{cm}$ DIN 51 581
Neutralization number	0,03 mg KOH/g DIN 51 777 T 1
Copper corrosion	0-1 DIN 51 809
Specific electrical volume resistance at 20 °C	$1,6 \cdot 10^9 \Omega \cdot \text{cm}$
Odor	charakteristisch / characteristic
Form	flüssig / liquid

Areas of application

Suitable for use on vehicle electronic and general electrical systems.



Application

Spray components before installing them. If the contacts are heavily corroded, allow the product to act for longer and rub off corrosion residues with a cloth or brush.

Note: After spraying on, allow a flash-off period of 10 min. before connecting the component to a power supply.

Comment

 **WARNING:** Cancer- www.P65Warnings.ca.gov

Available pack sizes

140 g Can aerosol	20298 USA (-EN-)
-------------------	---------------------

Our information is based on thorough research and may be considered reliable, although not legally binding.