Product information

PI 12/28/01/2016

Motorbike Fork Oil 10W medium

Description

Full synthetic fork oil and shock-absorber oil. Has been developed for universal use. Special synthetic base oils and corresponding additives guarantee optimum drivability and damping. Prevents foam formation and seal hardening. Good corrosion and wear protection provide long service life.

Properties

- prevents seals from swelling
- prevents foam formation
- good corrosion protection
- high wear resistance
- better drivability

Technical data

Density at 15 °C	28,5 mm²/s ASTM D 7042-04
Viscosity at 40 °C	0,831 g/cm³ DIN 51757
Viscosity at 100 °C	5,7 mm²/s ASTM D 7042-04
Viscosity index	146 DIN ISO 2909
Pour point	-42 °C DIN ISO 3016
Flash point	244 °C DIN ISO 2592
Color number (ASTM)	L 0,5 DIN ISO 2049

Areas of application

Universal use in telescopic forks and shock absorbers on motorbikes, mopeds, autocycles and other two-wheeled vehicles.

Application

Follow the instructions of the telescopic fork, shock absorber and two-wheeled vehicle manufacturers.

Available pack sizes

500 ml Can plastic	1506 D-GB-I-E-P
500 ml Can plastic	7599 D-RUS-UA
500 ml Can plastic	5952 D-F-I-GR
1 l Can plastic	2715 D-GB-I-E-P
1 l Can plastic	20092 GB-F-E-USA-CAN
5 l Canister plastic	1606 D-GB-I-E-P
5 l Canister plastic	5953 D-F-I-GR
20 l Canister plastic	3828 D

Our information is based on thorough research and may be considered reliable, although not legally binding.

LIQUIMOLY GmbH
Jerg-Wieland-Str. 4
89081 Ulm-Lehr

Postfach 2829
89018 Ulm
Germany

Phone: +49 (0)731/1420-13
Fax: +49 (0)731/1420-82
e-mail: info@liqui-moly.de

Service-hotline: 0800/8323230
Technical hotline: +49 (0)731/1420-871
www.liqui-moly.de