

# Product information

## Motorbike Fork Oil 15W heavy

PI 20/27/08/2020



### Description

Full synthetic fork oil and shock-absorber oil. Reduces shear losses and provides sure handling performance even after long use. Prevents foam formation and seal hardening. Good corrosion and wear protection provide long service life.

### Properties

- high wear resistance
- prevents foam formation
- increases driving safety
- lasting corrosion protection
- prevents seals from swelling

### Technical data

Density at 15 °C	0,835 g/cm <sup>3</sup> DIN 51757
Viscosity at 40 °C	45 mm <sup>2</sup> /s ASTM D 7042-04
Viscosity at 100 °C	8,0 mm <sup>2</sup> /s ASTM D 7042-04
Viscosity index	151 DIN ISO 2909
Pour point	-36 °C DIN ISO 3016
Flash point	260 °C DIN ISO 2592
Color number (ASTM)	L 0,5 DIN ISO 2049

### Areas of application

Universal use in telescopic forks and shock absorbers on motorbikes, mopeds, autocycles and other two-wheel vehicles.

### Application

Follow the instructions of the telescopic fork, shock absorber and two-wheel vehicle manufacturers.



### Available pack sizes

500 ml Can plastic	1524 D-GB-I-E-P
500 ml Can plastic	5954 D-F-I-GR
1 l Can plastic	2717 D-GB-I-E-P

**Our information is based on thorough research and may be considered reliable, although not legally binding.**