

## Motorbike Fork Oil SAE 15W heavy



### Description

Full synthetic, high-viscosity fork or shock-absorber oil. Unique formulation prevents premature shear loss and provides full performance even after extended usage. Prevents foaming and maintains seals to prevent leaks. Long service life in combination with good corrosion and wear protection.

### Properties

- very wear resistant
- prevents foam formation
- increases driving safety
- lasting corrosion protection
- prevents seals from swelling

### Technical data

Density at 59 °F	0,835 g/cm <sup>3</sup> DIN 51757
Viscosity at 104 °F	45 mm <sup>2</sup> /s ASTM D 7042-04
Viscosity at 212°F	8,0 mm <sup>2</sup> /s ASTM D 7042-04
Viscosity index	151 DIN ISO 2909
Pour point	-33 °F DIN ISO 3016
Flash point	500 °F DIN ISO 2592
Color number (ASTM)	L 0,5 DIN ISO 2049

### Areas of application

Universal use in telescopic forks and shock absorbers on motorbikes and other powersport vehicles where an oil with current product specifications is required or recommended.

### Application

Observe the manufacturers instructions! Optimum effectiveness only when the product is used undiluted.

### Available pack sizes

1 l Can plastic	20096 USA AND CANADA (-EN-F-)
20 l Canister plastic	20405 USA AND CANADA (-EN-F-)

**Our information is based on thorough research and may be considered reliable, although not legally binding.**