

Silicone Spray

Description

Silicone Spray is a mineral-oil free, grease-free release agent, lubricant and protective coating based on silicones dissolved in chlorine-free solvents. Silicone Spray protects, lubricates and insulates all surfaces by means of a transparent, permanent protective film.

Properties

- eliminates unwanted noise
- impregnates
- pleasant odor
- outstanding release agent during inert gas shielded arc welding
- protects and cares for all plastics
- clean application
- insulates

Technical data

Base	Siliconöl, Spezialbenzin / silicone oil, special petrol
Propellant	Propan, Butan / propane, butane
Color / appearance	farblos / colourless
Density at 20 °C	0,58 g/cm ³
Form	aerosol, flüssig / aerosol, liquid
Odor	charakteristisch / characteristic

Areas of application

Release agent, lubricant and treatment and protective aid for plastics, rubber, metal and wood.

Application

Spray a thin and even coating onto the components to be treated and repeat the treatment if necessary. Do not work in the vicinity of painted areas. It must be ensured that Silicone Spray is not sprayed on food or on machine components which come into direct contact with food.



Available pack sizes

300 ml Can aerosol	3310 D-GB-I-E-P
300 ml Can aerosol	2899 GB-DK-FIN-N-S
300 ml Can aerosol	2665 D-PL-H-RO-TR
300 ml Can aerosol	3955 D-RUS-UA
400 ml Can aerosol	1835 D-NL-F-GR-ARAB

Our information is based on thorough research and may be considered reliable, although not legally binding.