

Oil Binder

Description

Powerful oil absorber based on 100 % polyurethane hard foam. The oil take-up capacity is barely reduced by any water present, so the product is almost 100 % effective. Complies with the requirements of Type I, II and III/SF with rating R (Announcement of the Federal Ministry for the Environment, Nature Conservation and Nuclear Safety dated 3/12/90 and 4/23/98 for Type I, II, RSF).

Properties

- residue-free combustion
- for indoor and outdoor use
- high spreading rate
- also suitable for breakdown recovery services and fire departments
- can also be used on wet surfaces
- binds oil, fuel and hydrophobic (water repellent) chemicals

Technical data

Form	Granulat / granular
Color / appearance	hellbraun, hellgelb / light brown, light yellow
Base	Polyurethan / polyurethane
Grain size	0,5 – 4 mm
Odor	geruchslos / odourless
Oil absorbency, per liter oil binder	1 l Ölbinder bindet 0,58 l Öl / 1 litre of Oil Binder binds 0.58 litres of oil
Apparent density	~296 g/l
Storage stability	>5 Jahre / >5 years
Flash point	~300 °C

Areas of application

Suitable for small and large areas inside and outside.

Application

Particularly with large-area applications, unknown liquids or mixtures, first check the compatibility of the absorbing liquid with LIQUI MOLY Oil Binder. Apply Oil Binder in a layer that is 5 mm thick on the liquid to be removed and remove after sufficient time for the product to take effect. Absorption effect can be improved and accelerated by sweeping back and forth with hard broom.

For use in conventional spreaders. When pouring the sack, please make note of the direction and strength of the wind as well as general protective measures. In



addition, the ignition hazards resulting from electrostatic charges must be observed.

According to the declaration by the Federal Ministry for the Environment, Nature Conservation and Nuclear Safety dated 3/12/1990 in GMBI no. 18 S. 337, sufficient cleaning of traffic areas requires at least two applications of binders and subsequent cleaning with a 1 % wetting agent solution and water. The wetting agent solution must be disposed of through reabsorption, where possible.

For disposal measures following use, observe the relevant regulations and legal specifications valid for the absorptively bound substance.

Available pack sizes

25 l Carton	7250
	D-GB-I-E-P

Our information is based on thorough research and may be considered reliable, although not legally binding.