

## A/C System Cleaner

### Description

Cleaning fluid for removing mold and bacteria (e.g. legionellae) from A/C systems in passenger cars, commercial vehicles, buses and in the home without the need for dismantling. After cleaning, this product leaves behind a pleasant fresh fragrance.

### Properties

- expert's microbiological report available
- removes musty smells
- assures fresh, clean air
- increases ride comfort
- forms a protective film
- destroys molds and bacteria
- cleans air inlet ducts

### Technical data

Base	Desinfektionsmittel, Geruchshemmer, Duftstoffe / disinfectant, odour remover, fragrances
Color / appearance	farblos / colourless
Density at 20 °C	1,0 g/ml
Odor	Zitrone / lemon
Form	flüssig / liquid
Shelf life	24 Monate in original verschlossenen Gebinden / 24 months in original sealed containers
Solvent content	0 %
pH value	7

### Areas of application

Used for cleaning and disinfecting air conditioning systems in passenger motor vehicles and commercial vehicles. The product can also be used for domestic air conditioning systems.

### Application

#### Packed in individual applications:

One pack will treat one vehicle or one air conditioning system. If the manufacturer of the air conditioning system offers a cleaning service recommendation, this recommendation must be observed. If no model-specific instructions are available from the passenger car manufacturer, follow the LIQUI MOLY recommendation for application. Spray the cleaning fluid directly on the surface of the evaporator (if possible) for commercial vehicle, bus and home air conditioning systems.



#### LIQUI MOLY recommended use:

- During the cleaning process, make sure the window is open and avoid inhaling the vapors
- Check to make sure that the condensation water drainage is not blocked
- Dry the surface of the evaporator for 10 minutes with the engine running using the following heater and blower settings: Switch off the air conditioning and set to air circulation mode. Set the air distribution switch to footwell. Turn the temperature regulator and blower selector to maximum

#### Cleaning the air conditioning system:

- Insert the cleaner probe toward the evaporator (center of the vehicle). See vehicle-specific instructions at [www.liqui-moly.de](http://www.liqui-moly.de).
  - Actuate the cleaner and move the spray probe carefully back and forth to flush out and clean the evaporator thoroughly with LIQUI MOLY Air Conditioning Cleaner.
  - Allow 15 - 20 minutes for the cleaner to take effect
  - Dry the surface of the evaporator for 10 minutes with the heater and blower at the same setting as prior to cleaning
  - Replace and insert dust and pollen filter
- Please note: Any cleaner which is spilled must be wiped up using a damp cloth and water.

#### Available pack sizes

250 ml Can aerosol	4087 D-GB-I-E-P
250 ml Can aerosol	2870 D-DK-FIN-N-S
250 ml Can aerosol	7577 D-RUS-UA
1 l Canister plastic	4091 D-GB-F-I-E-P
5 l Canister plastic	4092 D-GB-F-I-E-P

**Our information is based on thorough research and may be considered reliable, although not legally binding.**