

LM 49 Fluid Paste

Description

Ideal assembly, lubricating and running-in paste. For numerous applications in the manufacture, maintenance and servicing of motor vehicles, in agricultural applications, industry and construction machines. Very adherent. Penetration properties ensure excellent lubrication and optimal wear reduction, even with economic application. Very easy to use and thus particularly suitable for the workshop.

Properties

- highest load-carrying capacity
- outstanding emergency-running properties
- economical
- universal application
- good corrosion protection
- simple to use
- outstandingly adherent

Technical data

Color / appearance	schwarz / black
Base	Mineralöl / mineral oil
Additives	Kombination synthetischer Festschmierstoffe / combination of synthetic solid lubricants
Consistency	Thixotrop, bei Scherbeanspruchung flüssig / thixotropic, fluid under shear loading
Operating temperature range	30 bis +600 / 30 to +600 °C
Odor	charakteristisch / characteristic
Form	pastös, flüssig / pastelike, liquid
Density at 20 °C	1,2 g/cm ³
Flash point	>200 °C

Areas of application

Is exceptionally well-suited for the assembly, repair and maintenance of the entire motor vehicle. Can also be used in engineering and in industrial applications.

Application

Apply thinly onto surfaces which must be clean but not free of oil. Rubbing in not necessary. Can be applied in excess.



Available pack sizes

500 g Can sheet metal	3060
	D-GB-I-E-P

Our information is based on thorough research and may be considered reliable, although not legally binding.