

Product information

LM 145 Lubricant Compound

PI 10/26/02/2020



Description

Soft, extremely adherent lubricant for open drive elements. The film, which dries thoroughly, is especially suitable for open drives which are exposed to dust, water or weather.

Properties

- good water resistance
- stable under extreme pressures
- outstanding lubricating action
- good corrosion protection
- outstanding bond strength
- high shear stability
- high resistance to aging

Technical data

Color / appearance	schwarz / black
Water resistance at 90 °C	0 DIN 51 807
Base	hochviskoses Mineralöl / high-viscosity mineral oil
Operating temperature range	-30 bis +110 / -30 to +110 °C
Lubricants according to DIN 3536	MoS2 / bitumen
Density at 20 °C	0,673 g/cm ³
Flash point	-60 °C
Form	aerosol, flüssig / aerosol, liquid
Odor	charakteristisch / characteristic



Available pack sizes

300 ml Can aerosol	4020 D
--------------------	-----------

Our information is based on thorough research and may be considered reliable, although not legally binding.

Areas of application

For all lubrication points which are directly exposed to environmental conditions. For lubrication of gear-wheels, swing bearings, threaded spindles, chains, wire ropes, guideways and bearings. Used for agricultural and construction machinery, crane and conveyor plants and in shipping and transport companies.

Application

Apply thinly to cleaned lubrication point. Lubrication intervals will be found in the operation instructions. After use, clear spray nozzle by inverting can and spraying until only the propellant emerges.