

## Wax Coating

### Description

Extremely adherent, wax-based corrosion protection containing state-of-the-art agents. The adherent, permanently elastic and transparent protective film offers outstanding, reliable, long-term protection for inside and outside storage. Resistant to salt water and corrosive influences. The thin coating does not impair any subsequent welding work.

### Properties

- outstanding resistance to salt water
- excellent corrosion protection
- can be used for inside and outside storage
- excellent long-term protection
- transparent, adherent and waterproof protective film

### Technical data

Base	Wachs, Lösungsmittel / wax, solvents
Appearance / properties	hellbraun / light brown
Propellant	Propan, Butan / propane, butane
Density	0,7 g/ml DIN 51757
Film thickness	15-50 µm
Form	aerosol, flüssig / aerosol, liquid
Odor	charakteristisch / characteristic
Flash point	-60 °C

### Areas of application

For inside and outside storage, transport and dispatch of machines and metal components. The thin coating does not impair any subsequent welding work. Normal handling is possible soon after the non-oil-based film has been applied.

### Application

Shake can well before use and apply by spraying. The coating thickness is between 15 m and 50 m depending on environmental conditions. Apply to clean, dry surfaces. Apply several coats to increase protection against corrosion. The contents of the can should be at room temperature during application. When spraying in enclosed spaces, make sure that there is sufficient ventilation. **After use, clear spray nozzle by inverting can and spraying until only the propellant emerges.**



**Note: Engine compartment cleaner, part number 3326, can be used for removal of the wax coating. The application notes can be found in the product information for part no. 3326.**

### Available pack sizes

300 ml Can aerosol	3311
	D-GB-F-E-P-NL

**Our information is based on thorough research and may be considered reliable, although not legally binding.**