

Product information

LM 41 MoS2-Suspension

PI 14/25/06/2020



Description

The colloidal MoS₂ solid lubricant suspension in mineral oil reduces running-in and operating wear. The improved high pressure loading capability guarantees optimum emergency running properties and increases operational reliability. The MoS₂ solid lubricant reduces friction and lowers oil and fuel consumption.

Properties

- reduces oil and fuel consumption
- outstanding emergency-running properties
- highly economical
- miscible with all commercially available motor oils
- distinctive high-pressure characteristics
- reduces running-in and operating wear
- absolutely compatible with filters
- increases operational reliability
- high thermal stability

Technical data

Color / appearance	schwarz / black
Base	Solventraffinat / solvent raffinate
Operating temperature range	wie bei Mineralölen, MoS ₂ : über 400 / as with other mineral, MoS ₂ : above 400 °C
Solids content	5 %
Form	flüssig / liquid
Odor	charakteristisch / characteristic
Density at 20 °C	0,92 g/ml
Flash point	200 °C
Viscosity at 40 °C	290-300 mm ² /s

Areas of application

Added to the lubricating oils of engines, compressors, pumps, hydraulic plants, and industrial transmissions.

Application

Add 3-5 % to the lubricating oil. Additions up to 10 % possible under extreme load.



Available pack sizes

1 l Can sheet metal	4051
	D-GB-I-E-P

Our information is based on thorough research and may be considered reliable, although not legally binding.