

Product information

Grinding Paste

PI 20/01/07/2020



Description

For easy removal of weathered and dull layers of paint, coarse contamination, paint spray dust, scratches and surface cracks. The treated surfaces can then be painted directly. Silicone-free. Suitable for polishing machines.

The treated product contains biocides as protective agents. C(M)IT/MIT (3:1) [CAS:55965-84-9]

Properties

- suitable for polishing machines
- easy removal of weathered paint layers
- simple to use
- prepares surfaces for painting
- very high standard of quality

Technical data

Solubility	teilweise löslich in H2O / partially soluble in water
Form	pastös / pastelike
Density	~1 g/cm ³ DIN 51757
Base	Schleifmittel, Lösungsmittel / grinding agent, solvents
pH value	n.a.
Color / appearance	weiß / white
Flash point	>65 °C DIN ISO 2592
Odor	charakteristisch / characteristic
Viscosity at 20 °C	10000 - 15000 cP
Density at 20 °C	~1 g/cm ³ ISO 787-10
Shelf life in original sealed container	30 months

Areas of application

Especially for pretreating before paint jobs and to remove paint damage such as scratches and paint spray mist. Suitable for non-ferrous and metallic paint.

Application

Clean the surfaces to be treated. Then apply the paste with a well moistened cloth or sponge and treat the surface, applying slight pressure, until dirt, scratches and oxidation layers are removed. For subsequent paintwork care, apply Hard Wax or Gloss Polish Spray Wax from LIQUI MOLY.



Comment

Attention when working with polishing machines, as the grinding paste has a very abrasive effect.

Available pack sizes

300 g Tube plastic	1556
	D-GB-I-E-P

Our information is based on thorough research and may be considered reliable, although not legally binding.