

## Liquimate 8300 Seam Sealant gray



### Description

High-grade, 1-component, MS polymer-based, spray-able seam sealant. Free of isocyanate and silicone. Resistant to UV and mineral oils. With most commercially available paints, can be painted over wet-on-wet immediately (max. up to 2 hours).

### Properties

- waterproof
- free of isocyanate
- can be used without primer
- silicone-free
- permanently elastic after curing
- can be applied as a spray or with a brush
- outstanding rigidity
- broad adhesive spectrum
- odorless
- high resistance to aging
- resistant to mineral oils
- can be painted over wet-in-wet
- fast-drying
- professional repairs
- high adhesive strength
- easy to use
- sealing compound and sprayable seam sealant

### Technical data

Curing rate at 23 °C / 50 % rh	3 mm/24 h DIN 50 015
Skin formation time at 23 °C/50 % relative humidity	20 min DIN 50 015
Color / appearance	grau / grey
Elongation at break	250 %
Hardness, Shore A	47 DIN 53 505
Thermal stability after curing	-40 - +80 °C
Tensile strength	2,1 N/mm <sup>2</sup>
Form	pastös / pastelike
Odor	benzinartig / petrol-like
Curing system	härtet aus durch Luftfeuchtigkeit / cured by moisture in the air
Density at 20 °C	1,38 g/cm <sup>3</sup>
Base	MS-Polymer
Tear growth resistance	5,0 N/mm DIN 53515
Shelf life in original sealed container	18 months

### Technical data

Recommended storage temperature ≤ 25 °C

### Areas of application

For sealing seams during repairs to restore to original factory condition. Areas of application include the engine compartment, trunk and wheel housings.

### Application

Surfaces must be clean and free of grease. Can be painted over after application of the material with solvent- and water-based paints. It is recommended that you check the adhesion and compatibility with plastics and paints for the specific object.

### Available pack sizes

310 ml Cartridge plastic 6150  
D-GB-F-I-E-NL-P

**Our information is based on thorough research and may be considered reliable, although not legally binding.**