

Product information

megol Gasmotorenoel Synth SAE40



Description

Fully synthetic gas engine oil based on polyalphaolefines and active ingredients with a low ash content. This means that deposits due to the oil in the combustion chamber are avoided as far as possible and oil change intervals can be longer.

It can be used for gas engines that are subject to high stress, which operate on natural gas, sewage gas and landfill gas, and with or without a catalytic converter.

Properties:

- very good detergent-dispersant properties
- very high oxidation resistance
- adequate protection against nitration
- ensures a high wear protection
- average ash content
- average alkalinity

The instructions issued by the manufacturers are to be followed



Available pack sizes

20 l Canister plastic

Part no. 8703
D-GB

200 l Drum sheet metal

Part no. 8763
D-GB

Characteristic data

Viscosity at 40 °C	88 mm ² /s ASTM D 7042-04
Viscosity at 100 °C	13,3 mm ² /s ASTM D 7042-04
Viscosity at -25 °C	<7000 mPas DIN 51377
Viscosity index	152 DIN ISO 2909
Density at 15 °C	0,845 g/cm ³ DIN 51757
Flash point	254 °C DIN ISO 2592
Pour point	-36 °C DIN ISO 3016
Total base number	5,5 mg KOH/g DIN ISO 3771
Sulfate ash	0,5 g/100g DIN 51575
SAE class (engine oils)	10W-40 SAE J300